



Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 1/12
(30635990/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

RainBuster 500 Stone

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

Top Industrial, Inc.
15010 Keswick St.
Van Nuys, CA 91405

Telephone: 1-818-901-1313

Emergency telephone number

CHEMTREC: 1-800-424-9300

Other means of identification

Chemical family: sealant

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Acute Tox.	4 (Inhalation - vapour)	Acute toxicity
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Resp. Sens.	1	Respiratory sensitization
Skin Sens.	1	Skin sensitization
Carc.	2	Carcinogenicity
STOT RE	1	Specific target organ toxicity — repeated exposure

Label elements

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 2/12
(30635990/SDS_GEN_US/EN)

Pictogram:



Signal Word:
Danger

Hazard Statement:

H332	Harmful if inhaled.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe dust/gas/mist/vapours.
P201	Obtain special instructions before use.
P261	Avoid breathing vapours.
P202	Do not handle until all safety precautions have been read and understood.
P284	[In case of inadequate ventilation] wear respiratory protection.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314	Get medical advice/attention if you feel unwell.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P303 + P362	IF ON SKIN (or hair): Wash with plenty of soap and water.
P333 + P311	If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.
P362 + P364	Take off contaminated clothing and wash before reuse.
P337 + P311	If eye irritation persists: Call a POISON CENTER or doctor/physician.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 3/12
(30635990/SDS_GEN_US/EN)

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Labeling of special preparations (GHS):

SENSITIZATION CAN OCCUR IN SOME INDIVIDUALS, LEADING TO ASTHMA-LIKE SPASMS OF THE BRONCHIAL TUBES AND DIFFICULTY BREATHING. INDIVIDUALS WITH A HISTORY OF RESPIRATORY ILLNESS, ASTHMATIC CONDITIONS, EYE DAMAGE OR TDI SENSITIZATION SHOULD NOT BE EXPOSED TO THIS PRODUCT. TDI IS INCLUDED IN THE NTP ANNUAL REPORT ON CARCINOGENS. RESULTS FROM A TDI HEALTH STUDY INDICATE THAT OVEREXPOSURE TO A RESPIRATORY IRRITANT, RESULTING IN LOWER RESPIRATORY TRACT SYMPTOMS COULD INCREASE THE RISKS OF DEVELOPING ASTHMA-LIKE REACTIONS FROM SUBSEQUENT TDI EXPOSURE. ANIMAL TESTS AND OTHER RESEARCH INDICATE THAT SKIN CONTACT WITH MDI MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview

WARNING:

SENSITIZATION CAN OCCUR IN SOME INDIVIDUALS, LEADING TO ASTHMA-LIKE SPASMS OF THE BRONCHIAL TUBES AND DIFFICULTY BREATHING. INDIVIDUALS WITH A HISTORY OF RESPIRATORY ILLNESS, ASTHMATIC CONDITIONS, EYE DAMAGE OR TDI SENSITIZATION SHOULD NOT BE EXPOSED TO THIS PRODUCT. TDI IS INCLUDED IN THE NTP ANNUAL REPORT ON CARCINOGENS. RESULTS FROM A TDI HEALTH STUDY INDICATE THAT OVEREXPOSURE TO A RESPIRATORY IRRITANT, RESULTING IN LOWER RESPIRATORY TRACT SYMPTOMS COULD INCREASE THE RISKS OF DEVELOPING ASTHMA-LIKE REACTIONS FROM SUBSEQUENT TDI EXPOSURE.

Irritating to eyes, respiratory system and skin.

CONTAINS MATERIAL WHICH MAY CAUSE CANCER.

Avoid contact with the skin, eyes and clothing.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
1317-65-3	>= 15.0 - < 20.0 %	Limestone
13463-67-7	>= 3.0 - < 5.0 %	Titanium dioxide
14807-96-6	>= 3.0 - < 5.0 %	talc
1305-78-8	>= 1.0 - < 3.0 %	calcium oxide
8052-41-3	>= 1.0 - < 3.0 %	Stoddard solvent
91-08-7	>= 0.3 - < 1.0 %	toluene-2,6-diisocyanate
2530-83-8	>= 0.3 - < 1.0 %	trimethoxy(3-(oxiranylmethoxy)propyl)silane
584-84-9	>= 0.03 - < 0.04 %	toluene-2,4-diisocyanate

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
1317-65-3	>= 15.0 - < 20.0 %	Limestone
13463-67-7	>= 3.0 - < 5.0 %	Titanium dioxide
14807-96-6	>= 3.0 - < 5.0 %	talc
1305-78-8	>= 1.0 - < 3.0 %	calcium oxide
8052-41-3	>= 1.0 - < 3.0 %	Stoddard solvent
91-08-7	>= 0.3 - < 1.0 %	toluene-2,6-diisocyanate
2530-83-8	>= 0.3 - < 1.0 %	trimethoxy(3-(oxiranylmethoxy)propyl)silane
584-84-9	>= 0.037 - < 0.04 %	toluene-2,4-diisocyanate

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 4/12
(30635990/SDS_GEN_US/EN)

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

No applicable information available.

If on skin:

Wash thoroughly with soap and water. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 5/12
(30635990/SDS_GEN_US/EN)

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.
For large amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

Keep away from sources of ignition - No smoking. The relevant fire protection measures should be noted.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight. Store protected against freezing.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

toluene-2,6-diisocyanate	ACGIH TLV	TWA value 0.005 ppm ; STEL value 0.02 ppm ;
toluene-2,4-diisocyanate	OSHA PEL	CLV 0.02 ppm 0.14 mg/m ³ ; TWA value 0.005 ppm 0.04 mg/m ³ ; STEL value 0.02 ppm 0.15 mg/m ³ ;
	ACGIH TLV	TWA value 0.005 ppm ; STEL value 0.02 ppm ;
calcium oxide	OSHA PEL	PEL 5 mg/m ³ ; TWA value 5 mg/m ³ ;
	ACGIH TLV	TWA value 2 mg/m ³ ;

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 6/12
(30635990/SDS_GEN_US/EN)

Limestone	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
Titanium dioxide	OSHA PEL ACGIH TLV	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ; TWA value 10 mg/m3 ;
talc	OSHA PEL	TWA value 20 millions of particles per cubic foot of air ; TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$, using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits. TWA value 0.1 mg/m3 Respirable ; The exposure limit is calculated from the equation, $10/(\%SiO_2+2)$, using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits. TWA value 0.3 mg/m3 Total dust ; The exposure limit is calculated from the equation, $30/(\%SiO_2+2)$, using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits. TWA value 2 mg/m3 Respirable dust ; TWA value 0.3 mg/m3 Total dust ; The exposure limit is calculated from the equation, $30/(\%SiO_2+2)$, using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits. TWA value 0.1 mg/m3 Respirable ; The exposure limit is calculated from the equation, $10/(\%SiO_2+2)$, using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits. TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$, using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits. TWA value 20 millions of particles per cubic foot of air ;
	ACGIH TLV	TWA value 2 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
Stoddard solvent	OSHA PEL ACGIH TLV	PEL 500 ppm 2,900 mg/m3 ; TWA value 100 ppm ;

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 7/12
(30635990/SDS_GEN_US/EN)

Personal protective equipment

Respiratory protection:

No applicable information available.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. No special measures necessary if stored and handled correctly. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	paste	
Odour:	mild	
Odour threshold:		No applicable information available.
Colour:	tan to brown	
pH value:		neutral
Melting point:		No applicable information available.
Boiling point:		No applicable information available.
Sublimation point:		No applicable information available.
Flash point:		Non-flammable.
Flammability:	not flammable	(UN Test N.1 (ready combustible solids))
Lower explosion limit:		No applicable information available.
Upper explosion limit:		No applicable information available.
Autoignition:		No applicable information available.
Vapour pressure:		The product has not been tested.
Density:	approx. 10.1 lb/USg	(25 °C)
Relative density:		No applicable information available.
Vapour density:		No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):		No applicable information available.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:		No applicable information available.
Viscosity, kinematic:		No applicable information available.
Solubility in water:		(15 °C) insoluble
Miscibility with water:		(15 °C) not (e.g. <10%)
Solubility (quantitative):		No applicable information available.
Solubility (qualitative):	No applicable information available.	
Evaporation rate:		No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 8/12
(30635990/SDS_GEN_US/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Of very high toxicity after short-term inhalation. Of low toxicity after single ingestion.

Oral

Type of value: ATE

Value: > 5,000 mg/kg

Inhalation

Type of value: ATE

Value: 14.8 mg/l

Determined for vapor

Dermal

Type of value: ATE

Value: > 5,000 mg/kg

Assessment other acute effects

No applicable information available.

Irritation / corrosion

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 9/12
(30635990/SDS_GEN_US/EN)

Assessment of irritating effects: The product has not been tested. The statement has been derived from the properties of the individual components.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible. The substance may cause sensitization of the respiratory tract.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Prolonged exposure may cause chronic effects.

Genetic toxicity

Assessment of mutagenicity: The substance was mutagenic in various bacterial test systems; however, a mutagenic effect could not be confirmed in mammalian cell culture.

Carcinogenicity

Assessment of carcinogenicity: Contains a compound classified as IARC Group 2B (possibly carcinogenic to humans).

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Information on: toluene-2,6-diisocyanate

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies gave no indication of a fertility impairing effect.

Teratogenicity

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 10/12
(30635990/SDS_GEN_US/EN)

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Poorly biodegradable.

The product is unstable in water. The elimination data also refer to products of hydrolysis.

Assessment biodegradation and elimination (H2O)

Information on: TDI

Poorly biodegradable. The product is unstable in water. The elimination data also refer to products of hydrolysis.

Mobility in soil

Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

Additional information

Other ecotoxicological advice:

Acutely harmful for aquatic organisms. Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 11/12
(30635990/SDS_GEN_US/EN)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Acute; Chronic

EPCRA 313:

<u>CAS Number</u>	<u>Chemical name</u>
91-08-7	toluene-2,6-diisocyanate

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
5000 LBS	7664-38-2	phosphoric acid
1000 LBS	108-88-3	Toluene
100 LBS	108-90-7; 584-84-9; 91-08-7	chlorobenzene; toluene-2,4-diisocyanate; toluene-2,6-diisocyanate

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
MA, NJ, PA	1317-65-3	Limestone
MA, NJ, PA	13463-67-7	Titanium dioxide
MA, NJ, PA	14807-96-6	talc
MA, NJ, PA	1305-78-8	calcium oxide
MA, NJ, PA	8052-41-3	Stoddard solvent
MA, NJ, PA	91-08-7	toluene-2,6-diisocyanate
MA, NJ, PA	584-84-9	toluene-2,4-diisocyanate

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health : 2 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 2[□] Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

Top Industrial, Inc.
SDS Prepared on: 2014/12/16

Safety Data Sheet

RainBuster 500 Stone

Revision date : 2014/12/16
Version: 1.0

Page: 12/12
(30635990/SDS_GEN_US/EN)

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET