

RAIN[®] BUSTER

200

SUPERIOR BUTYL RUBBER CAULK

Top Industrial, Inc.
15010 Keswick St.
Van Nuys, CA 91405
Ph: 800-473-1617

Technical Data Sheet

Product Description:

Top Industrial's RainBuster 200 Butyl Rubber Caulk is a high quality, general purpose skinning butyl caulk. It offers outstanding leak prevention in a variety of industries and uses. It is ideal in OEM and construction applications where long term flexibility and excellent adhesion to varied surfaces including wood, glass, masonry, varied metals, and many plastics is required.

Features:

- Formulated with High Quality Butyl Rubber
- Outstanding Leak Prevention
- Excellent Weathering Resistance
- Superior Adhesion
- Remains Flexible
- Conforms to Federal Specification TT-S-001657 (standard for single component, butyl rubber compounds)
- USDA Accepted: This product is chemically acceptable as a sealant for the use in official establishments operating under the Federal Meat and Poultry Products Inspection Program. The compound must be used in a manner which prevents direct or indirect contamination of edible products.

Technical Data:

Shore A Hardness: 30-35

Tensile Strength: 125 psi

Tack Free Time: Within 3 hours

Cure Time: 7-10 days at 72°F

Service Temperature: -20°F to 180°F

Water Resistance (AAMA 808): No voids, cracks, separation, or breakdown after water exposure.

Adhesion (ASTM C794): Excellent

VOC Content (per EPA Method 24): 106 g/L

Storage: For maximum shelf life, store unopened product at or below 80°F

Application: Surfaces must be clean, dry, and free of contaminants. Cut tip at 45° angle at desired bead size and puncture seal. Apply with quality caulking gun. Field test to insure satisfaction before proceeding with full application or project.

Available Colors: White, Gray

Painting: Once cured, RainBuster 200 may be painted with most industrial and commercial paints. Please conduct field test to insure satisfaction.

Read Safety Data Sheet (SDS) prior to use.