# 420 · 420 · 420 · 420

Part of the ...
RainBuster
LEAK-FREE

# RAIN BUSTER



## **Nail On Flashing Membrane**

### Self-Seals Around Fasteners







#### WINDOW & DOOR INSTALLATIONS | LATH & PLASTERING, SHEET METAL, AND FRAMING APPLICATIONS

RainBuster 420 Nail On Flashing Membrane is an ultra high performance flashing product ideal for use in window & door installation, lath & plastering, sheet metal, waterproofing, and framing. Its innovative technology provides industry best leak prevention.

RainBuster 420 combines the ease of use and versatility of a mechanically attached flashing with the self-sealing characteristics of a rubberized asphalt peel & stick. In fact, RainBuster 420, with its three permanent layers of protection, is neither a peel & stick nor a traditional mechanically attached flashing. Its unique design is comprised of an inner core of high quality rubberized asphalt encapsulated by two permanently adhered high performance films.

When penetrated, the rubberized asphalt core is designed to self-seal around the shank of the fastener, providing added protection against water intrusion. RainBuster 420 is the ultimate flashing material, providing ease of use, durability, strength, and self-sealing.

RainBuster 420 is part of the RainBuster LEAK-FREE Window Installation System. It is fully compatible with RainBuster window installation sealants.

- ▶ Ease of Use Provides Labor Savings
- Nail On Installation Nothing to Peel
- Three Layers of Protection
- ▶ Heavy-Duty Design Withstands High Winds and Job Site Abuse
- Superior Self-Sealing Around Fasteners
- For Sheeted or Open Wall Construction
- Can be Installed in all Weather Conditions
- ▶ UV Resistant Approved for 120 Day Exposure
- ➤ A Part of the RainBuster LEAK-FREE Window Installation System
- Outstanding Product and System Warranties (see reverse)

## **Self-Sealing Protection**



# <u>420 • 420 • 420 • 420 • 420</u>

## RAIN BUSTER

## Nail On Flashing Membrane

**Self-Seals Around Fasteners** 

WINDOW & DOOR INSTALLATIONS | LATH & PLASTERING, SHEET METAL, AND FRAMING APPLICATIONS

#### **DESCRIPTION**

RainBuster 420 Nail On Flashing Membrane is an ultra high performance flashing material for use in varied waterproofing applications and industries. Its unique design features a self-sealing, rubberized asphalt core encapsulated by two permanent films (a white cross laminated polyethylene and a metallized polyester). RainBuster 420 is available in 25 mil thickness, in 9" and 12" widths, on 75' rolls.

**FEATURES:** RainBuster 420's unique design combines the ease of use of nail on flashings with the self-sealing and waterproofing characteristics of membrane flashings. RainBuster 420 is installed with mechanical fasteners.

APPROPRIATE SURFACES: RainBuster 420 can be installed on any surface that can accept a mechanical fastener.

APPLICATION: Install white side (logo printed side) out. Follow Top Industrial recommended installation procedures, industry accepted standards including AAMA and ASTM, window manufacturer recommendations, and applicable building codes. Contact Top Industrial for additional information.

**USE WITH SEALANTS:** RainBuster 450 Window & Door Sealant is ideal for use with this product. Unrestricted contact between RainBuster Sealant and this product is acceptable.

UV LIGHT EXPOSURE: May be left exposed to UV light and direct sunlight (after installation and prior to completion of building process) for up to 120 days. Take steps to protect installed RainBuster 420 Flashing from long-term UV Light exposure. When construction process is complete, RainBuster 420 should be inside closed structure, beneath exterior cladding.

**SERVICE TEMPERATURE:** RainBuster 420's rubberized asphalt formulation provides a service temperature of 180°F, up to which it will maintain functional stability and will not run, slump, or drip.

**LIMITATIONS:** RainBuster 420 should not be installed behind metal cladding systems (siding, panels, etc..) or behind metal roofing systems.

**STORAGE:** Keep in cool, dry place that is shielded from weather and direct sunlight.

RAINBUSTER LEAK-FREE SYSTEMS: RainBuster 420 is part of the RainBuster LEAK-FREE Window Installation Systems. These systems combine RainBuster 450 Sealant, RainBuster Flashing(s), and RainBuster recommended installation procedures. Contact Top Industrial for additional information.



**30 YEAR WINDOW INSTALLATION SYSTEM WARRANTY:** When RainBuster 420 is used in combination with RainBuster 450 Sealant and RainBuster recommended installation procedures, a 30 Year Parts & Labor warranty is provided. Contact Top industrial for additional information.

LIMITED LIFETIME PRODUCT WARRANTY: Top Industrial, Inc. warrants this flashing product to perform as described on its package and associated data sheet for a period of 100 years from the date of purchase. Upon proof of purchase, Top Industrial's sole liability, expressed or implied, shall be to replace product proven defective and is limited to the stated selling price. This warranty is not transferable from the original purchaser. In no event shall Top Industrial be liable for consequential or incidental damages, resulting from the use of its products.

#### PERFORMANCE PROPERTIES:

Thickness	25 mil
Available Widths	9" and 12"
Roll Length	75'
Tensile Strength ASTM D412	580 psi
Elongation ASTM D412	130%+
Pliability ASTM D146	PASS
Compound Stability ASTM D5147	180°F
Service Temperature	180°F

TRUSTED
RAINBUSTER
QUALITY
bra

For more than 25 years, Top Industrial's RainBuster

brand has been trusted to prevent leaks in the building envelope and squeaks in floor structures. Today that trust runs deep - RainBuster is specified by the nation's leading builders and trusted by scores of respected contractors.

The reason for the trust is simple...

RainBuster products and services outperform other brands in preventing leak and squeak related call-backs. **DISTRIBUTED BY:**