

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

SECTION 1. IDENTIFICATION

Product name : RainBuster 900 Stone

Product code : TOP900STN

Manufacturer or supplier's details

Company name of supplier : Top Industrial, Inc.

Address : 15010 Keswick St.

Van Nuys, CA 91405

Emergency telephone : CHEMTREC: +1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Acute toxicity (Inhalation -

vapour)

: Category 4

Serious eye damage/eye

irritation

Category 2A

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity : Category 2

Specific target organ toxicity

- repeated exposure

Category 1 (Central nervous system)

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

H317 May cause an allergic skin reaction.

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

H351 Suspected of causing cancer.

H372 Causes damage to organs (Central nervous system)

through prolonged or repeated exposure.

Precautionary Statements

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust or mist.

P201 Obtain special instructions before use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P202 Do not handle until all safety precautions have been read and understood.

P284 In case of inadequate ventilation wear respiratory protection

P270 Do not eat, drink or smoke when using this product.

P264 Wash face, hands and any exposed skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P314 Get medical advice/ attention if you feel unwell. P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME

Version Revision Date: SDS Number: Date of last issue: -

Date of first issue: 10/20/2020 1.0 10/20/2020 000000695241

INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Sealant

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 15 - < 20
Titanium dioxide	13463-67-7	>= 3 - < 5
talc	14807-96-6	>= 3 - < 5
calcium oxide	1305-78-8	>= 1 - < 3
Stoddard solvent	8052-41-3	>= 1 - < 3
toluene-2,6-diisocyanate	91-08-7	>= 0.3 - < 1
trimethoxy(3- (oxiranylmethoxy)propyl)silane	2530-83-8	>= 0.3 - < 1

SECTION 4. FIRST AID MEASURES

General advice Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance

Do not leave the victim unattended.

If inhaled No applicable information available.

Call a physician or poison control center immediately.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact Immediately flush eye(s) with plenty of water.

> Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

Causes serious eve irritation.

Harmful if inhaled.

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Hazardous combustion prod-

ucts

harmful vapours

nitrogen oxides fumes/smoke carbon black

Further information : Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Special protective equipment

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Avoid dust formation. Avoid breathing dust.

Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid formation of respirable particles.

Do not breathe vapors/dust.

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/20/2020	000000695241	Date of first issue: 10/20/2020

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, well-ventilated

place.

Protect from direct sunlight.
Store protected against freezing.

Materials to avoid : Observe VCI storage rules.

Further information on stor-

age stability

No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
toluene-2,6-diisocyanate	91-08-7	STEL value (Inhalable fraction and vapor)	0.005 ppm	ACGIHTLV
		Skin Desig- nation (In- halable frac- tion and va- por)		ACGIHTLV
		TWA value (Inhalable fraction and vapor)	0.001 ppm	ACGIHTLV
		С	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhal- able fraction and vapor)	0.001 ppm	ACGIH

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0
calcium oxide	1305-78-8	TWA value	2 mg/m3	ACGIHTLV
		REL value	2 mg/m3	NIOSH
		PEL	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	2 mg/m3	ACGIH
		TWA	2 mg/m3	NIOSH REL
		TWA	5 mg/m3	OSHA Z-1
		TWA	5 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respir- able fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respir- able dust fraction)	5 mg/m3	OSHA P0
		TWA (Res- pirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)

VersionRevision Date:SDS Number:Date of last issue: -1.010/20/2020000000695241Date of first issue: 10/20/2020

		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		TWA (Dust)	20 Million parti- cles per cubic foot	OSHA Z-3
		TWA (respir- able dust fraction)	2 mg/m3	OSHA P0
		TWA (Res- pirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	2 mg/m3	ACGIH
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIHTLV
		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		PEL	500 ppm 2,900 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0

Engineering measures : Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection : No applicable information available.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Protective measures : Avoid contact with the skin, eyes and clothing.

No special measures necessary if stored and handled cor-

rectly.

Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : tan to brown

Odor : mild

Odor Threshold : No data available

pH : neutral

Melting point : No applicable information available.

Boiling point : No applicable information available.

Flash point : does not flash

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not flammable

Method: Manual of tests and criteria. Test N.1 (United Nations Recommendations on the Transport of Dangerous Goods).

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure : No data available

Relative vapor density : No applicable information available.

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

Relative density : No applicable information available.

Density : approx. 10.1 lb/USg (77 °F / 25 °C)

Solubility(ies)

Water solubility : insoluble (59 °F / 15 °C)

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

: No applicable information available.

Autoignition temperature : No applicable information available.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Self-heating substances : No data available

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids Strong bases

Strong oxidizing agents

Strong oxidizing agents
Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Product:

Acute oral toxicity : ATE: > 5,000 mg/kg

Acute inhalation toxicity : ATE: 14.8 mg/l

Remarks: Determined for vapor

Acute dermal toxicity : ATE: > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

Components:

Titanium dioxide:

Not applicable

talc:

Not applicable

calcium oxide:

Not applicable

toluene-2,6-diisocyanate:

Not applicable

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Titanium dioxide:

Partition coefficient: n-

octanol/water

Remarks: Not applicable

talc:

Partition coefficient: n-

octanol/water

Remarks: Not applicable

calcium oxide:

Partition coefficient: n-

octanol/water

: Remarks: The value has not been determined because the

substance is inorganic.

Stoddard solvent:

Partition coefficient: n-

octanol/water

log Pow: 3.5 - 6.4 (68 °F / 20 °C)

Method: Partition coefficient (n-octanol/water), HPLC method.

toluene-2,6-diisocyanate:

Version **Revision Date:** SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

Partition coefficient: n-

log Pow: 3.74 Method: other (calculated) octanol/water

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

There is a high probability that the product is not acutely

harmful to aquatic organisms.

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging should be emptied as far as possible Contaminated packaging

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

toluene-2,6diisocyanate 91-08-7

US State Regulations

Pennsylvania Right To Know

calcium oxide	1305-78-8
Limestone	1317-65-3
Titanium dioxide	13463-67-7
talc	14807-96-6
Stoddard solvent	8052-41-3
4-methyl-m-phenylene diisocyanate	584-84-9

New Jersey Right To Know

calcium oxide	1305-78-8
Limestone	1317-65-3
Titanium dioxide	13463-67-7
talc	14807-96-6
Stoddard solvent	8052-41-3
toluene-2,6-diisocyanate	91-08-7

California Prop. 65

WARNING: This product can expose you to chemicals including toluene-2,6-diisocyanate, which is/are known to the State of California to cause cancer, and

toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory


SECTION 16. OTHER INFORMATION

Further information

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1) 1910.1000

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z-

1-A) / TWA value

Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIHTLV / Skin Designa: Skin Designation:

tion

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL): ACGIHTLV / TWA value : Time Weighted Average (TWA):

NIOSH / Ceil Time : Ceiling Limit Value and Time Period (if specified):

NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit
OSHA Z-1 / TWA : 8-hour time weighted average

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

OSHA Z-1 / C : Ceiling

OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response. Compensation, and Liability Act: CMR - Carcinogen, Mutagen or Reproductive Toxicant: DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 10/20/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/20/2020 000000695241 Date of first issue: 10/20/2020

WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN