



High Performance Air Barrier & Building Wrap

- › New Construction
- › Multi-Family & Custom Homebuilding
- › For Use with RainBuster Installation Guidelines

RainBuster 550 is a superior air barrier & building wrap that provides world class envelope protection. As part of the RainBuster Leak Free Weatherization System, it provides superior, best-in-class wall protection against water and air infiltration. Installed behind exterior cladding, its sophisticated design repels air and water yet remains breathable. As a secondary barrier, RainBuster 550 promotes dry wall structures and protection against the effects of condensation, mold growth, and water damaged framing.

Features

- The Ultimate in Performance
- Non-Woven, Non-Perforated
- Superior Water Resistance
- Certified Air Barrier and Building Wrap
- Provides Ideal, Balanced Breathability
- Superior Tear Strength



RAIN BUSTER

550

High Performance Air Barrier & Building Wrap

Overview:

RainBuster 550 is a high performance, non-woven, non-perforated air barrier & building wrap. Each of its performance attributes has been designed to provide superior, long-term leak prevention. It is ideal for production and custom new construction specifications.

Authorizations:

- Meets or Exceeds ASTM E2556, ICC-ES AC 38, and ASTM E2178
- 95%+ Drainage Efficiency
- Certified Air Barrier
- Perm Rating: 18
- Rated for 180-day UV Exposure
- Flame Spread Rating: Excellent, Class A (ASTM E84)
- Available Enhanced System Warranty

Availability: RainBuster 550 High Performance Air Barrier & Building Wrap is available in 9' x 150' rolls (56 rolls per pallet) and 5' x 200' rolls (42 rolls per pallet).

Storage: Store in a cool, dry place.

Ideal Uses: RainBuster 550 is ideal for use as an air barrier and building wrap on varied structures including single and multi-family residential, and custom homes. It is designed for use behind various cladding including siding, stucco and brick. RainBuster 550 is part of the RainBuster Leak-Free Weatherization System which includes the RainBuster Window Installation System (sealant, flashing, procedures), and RainBuster 900 polyurethane sealant for sealing penetrations in the building wrap.

Installation: Please see RainBuster 550 Installation Guidelines for details. For professional use only. Top Industrial offers complimentary expert field support & training to architects, builders, consultants, and installers. Visit topindustrial.com for installation guidelines.

Limited Lifetime Warranty: Top Industrial, Inc. warrants this product to perform as described on its package and associated data sheet for a period of 100 years from the date of purchase. Upon proof of purchase, Top Industrial's sole liability, expressed or implied, shall be to replace product proven defective and is limited to the stated selling price. This warranty is not transferable from the original purchaser. In no event shall Top Industrial be liable for consequential or incidental damages, resulting from the use of its products.

Enhanced System Warranty: When RainBuster 550 is used as part of the complete RainBuster Leak Free Weatherization System, a 30 Year Parts & Labor System Warranty is provided. To qualify, RainBuster 550 must be installed according to RainBuster 550 Installation Guidelines, and must be used in combination with the RainBuster Window Installation System (RainBuster 450 Sealant, RainBuster Flashing(s), and RainBuster installation procedure). Please contact Top Industrial for additional information.

Part of the **RainBuster®**
LEAK-FREE
Weatherization System

RainBuster 550 is part of the RainBuster Leak-Free Weatherization System. It is designed to integrate with the RainBuster Window Installation System, and RainBuster sealant and flashing, to provide a complete specified envelope solution. Use of the complete system results in a 30 Year Parts & Labor System Warranty.



July, © 2026