

Leak Proof TECHNOLOGY

RAIN BUSTER®

Since 1983



550

High Performance Air Barrier & Building Wrap



RainBuster 550 is a superior air barrier & building wrap that provides world class envelope protection. As part of the RainBuster Leak Free Weatherization System, it provides superior, best-in-class wall protection against water and air infiltration. Installed behind exterior cladding, its sophisticated design repels air and water yet remains breathable. As a secondary barrier, RainBuster 550 promotes dry wall structures and protection against the effects of condensation, mold growth, and water damaged framing.

Features:

- The Ultimate in Performance
- Non-Woven, Non-Perforated
- Superior Water Resistance
- Certified Air Barrier
- Provides Ideal, Balanced Breathability
- Superior Tear Strength
- Rated for Six Month UV Exposure
- Meets or Exceeds ICC-ES AC 38 and ASTM E 2178



Our leak & squeak eliminating systems feature high performance sealants, adhesives, flashings, tapes, and building wraps for the entire home.

Top Industrial, Inc. • 15010 Keswick St., Van Nuys, CA 91405 • 800.473.1617 • topindustrial.com

550

RAIN BUSTER®

#1 BUILDER
SPECIFIED

Since 1983



RainBuster 550 is part of the RainBuster Leak Free Weatherization System. It is designed to integrate with the RainBuster Window Installation System, and RainBuster sealant and flashing, to provide a complete specified envelope solution. Use of the complete system results in a 30 Year Parts & Labor System Warranty.

Availability: RainBuster 550 High Performance Air Barrier & Building Wrap is available in 9' X 150' rolls (42 rolls per pallet) and 5' X 200' rolls (36 rolls per pallet).

Storage: Store in a cool, dry place.

Authorizations: Complies with ICC-ES AC 38 and ASTM E 2178.

Ideal Uses: RainBuster 550 is ideal for use as an air barrier and building wrap on varied structures including single and multi-family residential, and custom homes. It is designed for use behind various cladding including siding, stucco and brick. RainBuster 550 is part of the RainBuster Leak Free Weatherization System which includes the RainBuster Window Installation System (sealant, flashing, procedures), and RainBuster 900 polyurethane sealant for sealing penetrations in the building wrap.

Installation: Please see RainBuster 550 Installation Guidelines for details. For professional use only. Top Industrial offers complimentary expert field support & training to architects, builders, consultants, and installers. Please contact Top Industrial for additional information.

Enhanced System Warranty: When RainBuster 550 is used as part of the complete RainBuster Leak Free Weatherization System, a 30 Year Parts & Labor System Warranty is provided. To qualify, RainBuster 550 must be installed according to RainBuster 550 Installation Guidelines, and must be used in combination with the RainBuster Window Installation System (RainBuster 450 Sealant, RainBuster Flashing(s), and RainBuster installation procedure). Please contact Top Industrial for additional information.

Limited Lifetime Warranty: Top Industrial, Inc. warrants this product to perform as described on its package and associated data sheet for a period of 100 years from the date of purchase. Upon proof of purchase, Top Industrial's sole liability, expressed or implied, shall be to replace product proven defective and is limited to the stated selling price. This warranty is not transferable from the original purchaser. In no event shall Top Industrial be liable for consequential or incidental damages, resulting from the use of its products.

| 550 | | Performance Specifications | |
|---|--|---|--|
| Construction | | Non-Woven, Non-Perforated Building Wrap | |
| Basis Weight, ASTM D 5261 | | 100 GSM | |
| Tear Strength (MD/CD), ASTM D 5733 | | 21/23 lbf | |
| Breaking Strength, ASTM D 5034 | | 55/50 lbf | |
| Hydrostatic Resistance, AATCC 127 | | 500 cm | |
| Water Resistance, ASTM D 779 | | 60 minutes | |
| Water Vapor Permeance, ASTM E 96, Method A | | 18 perms | |
| Water Ponding, ICC-ES AC 38 | | Pass | |
| Air Resistance, ASTM E 2178 | | <0.02 L/s/m ² @ 75 Pa | |
| ICC-ES AC 38 Compliance | | Yes | |
| UV Exposure Rating | | 6 Months | |

Our leak & squeak eliminating systems feature high performance sealants, adhesives, flashings, tapes, and building wraps for the entire home.

Top Industrial, Inc. • 15010 Keswick St., Van Nuys, CA 91405 • 800.473.1617 • topindustrial.com