

# RAIN BUSTER<sup>®</sup>

## Safety Data Sheet

### RainBuster 675

This safety data sheet complies with the requirements of: 29CFR1910.1200

**Issue Date** 05-Sep-2023

**Revision Date** 05-Sep-2023

**Version** 1

#### Product identifier

**Product Name** RainBuster 675 Thermoplastic Elastomeric Sealant Clear

#### Other means of identification

**Product Code** TOP675CLR

#### Recommended use of the chemical and restrictions on use

**Recommended Use** Sealant.

**Uses advised against** For exterior use only. Do not use indoors.

#### Details of the supplier of the safety data sheet

Top Industrial, Inc.  
15010 Keswick Street  
Van Nuys, CA 91405  
(800) 473-1617

#### Emergency telephone number

**Emergency Telephone** Call CHEMTREC Day or Night:  
Within USA and Canada: 1-800 424-9300

## 2. HAZARDS IDENTIFICATION

#### Classification

#### **OSHA Regulatory Status**

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 3

#### Label elements

#### **Emergency Overview**

**Danger**

#### **Hazard statements**

Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
May be fatal if swallowed and enters airways  
Flammable liquid and vapor



**Appearance** Viscous **Physical state** Paste/Gel **Odor** Solvent (Mineral Spirits) Aromatic

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 Specific treatment (see first aid information on this label)  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Harmful to aquatic life

Unknown acute toxicity 35% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substance**

**Mixture**

This product is a mixture.  
 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Common name** Sealant and Caulk.  
**Synonyms** SEALANT.  
**Chemical nature** Organic solvents and additives.

Chemical Name	CAS No.	Weight-%	Trade Secret
Hydrocarbon Resin	69430-35-9	30 - 40%	*
Styrene/Butadiene Copolymer	66070-58-4	20 - 30%	*

Aromatic Naptha (with <0.1% Benzene)	64742-95-6	20 - 30%	*
1,2,4 Trimethylbenzene	95-63-6	10 - 20%	*
Xylene	1330-20-7	0 - 10%	*
Cumene	98-82-8	0 - 10%	*

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	Contains petroleum distillate. Harmful or fatal if swallowed. Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
<b>Eye contact</b>	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
<b>Skin contact</b>	Wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.
<b>Inhalation</b>	Move to fresh air in case of accidental inhalation of vapors. If continued difficulty with breathing is experienced, get medical attention immediately.
<b>Ingestion</b>	Not an expected route of exposure. If swallowed, do not induce vomiting. Get medical attention immediately.
<b>Self-protection of the first aider</b>	First aider: Pay attention to self-protection!.

##### Most important symptoms and effects, both acute and delayed

**Symptoms** May cause skin irritation. May cause eye irritation.

##### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Sand. Use foam or water FOG as a last resort.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Sealed container may rupture/burst when heated or exposed to excessive heat.

**Hazardous combustion products** Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

##### Explosion data

**Sensitivity to Mechanical Impact** Not sensitive.

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** No action should be taken involving any personal risk or without suitable training. Use personal protective equipment as required.

**Other Information** Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).

**For emergency responders** Use personal protection recommended in Section 8.

**Environmental precautions**

**Environmental precautions** Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent product from entering sewers, drains, or waterways. Local authorities should be advised if significant spillages can not be contained. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Contain spillage with non-combustible absorbent material, e.g. sand, earth, diatomaceous earth, vermiculite.

**Methods for cleaning up** Pick up the absorbed material (described just above) and transfer to properly labeled containers for disposal according to local / national regulations (see Section 13).

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Use personal protective equipment as required. Remove all sources of ignition. Use only outdoors.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep containers tightly closed in a cool, dry, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition.

**Incompatible materials** Strong acids. Strong oxidizing agents.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Use natural cross ventilation, local (mechanical) pick-up, and/or general area mechanical cross ventilation. Ventilation pattern should be designed to prevent accumulation of vapors. Ventilation must be sufficient to maintain vapor concentrations below the TWA limits outlined above.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing that is resistant to chemical penetration.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respiratory protection should be worn.

**General Hygiene Considerations** Wash face, hands and any exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical state</b>	Paste/Gel	<b>Odor</b>	Solvent (Mineral Spirits)
<b>Appearance</b>	Viscous		Aromatic
<b>Color</b>	Clear	<b>Odor threshold</b>	1-30 PPM. Odor thresholds vary greatly. Do not rely on odor threshold alone to determine potentially hazardous substances.

<b><u>Property</u></b>	<b><u>Values</u></b>	<b><u>Remarks • Method</u></b>
<b>pH</b>	Not applicable	
<b>Melting point/freezing point</b>	None / -70 276F None / -94 °F	Melting Point is not applicable. Freezing points are shown.
<b>Boiling point / boiling range</b>	> 154 276F / 310 °F	
<b>Flash point</b>	> 40.5 276F / > 105 °F	Setaflash
<b>Evaporation rate</b>	0.1	Butly acetate = 1
<b>Flammability (solid, gas)</b>	N/A	
<b>Flammability Limit in Air</b>		Flammable above 105 degrees F and 40.5 degrees C.
<b>Upper flammability limit:</b>	7.0	
<b>Lower flammability limit:</b>	1.6	
<b>Vapor pressure</b>	0.3 (kPa)	@ 20 °C
<b>Vapor density</b>	5.3	Where: Air = 1 at 68 degrees F (20 degrees C)
<b>Specific Gravity</b>	0.95-1.05	Water = 1g/ml
<b>Water solubility</b>	Insoluble	
<b>Solubility in other solvents</b>	Soluble in aromatic and aliphatic solvents.	
<b>Partition coefficient</b>	N/A	No data available.
<b>Autoignition temperature</b>	330 276F / 626 °F	
<b>Decomposition temperature</b>	N/A	
<b>Kinematic viscosity</b>	N/A	
<b>Dynamic viscosity</b>	N/A	
<b>Explosive properties</b>	Vapor accumulation could flash or explode if ignited.	
<b>Oxidizing properties</b>	None	

**Other Information**

Softening point	Not applicable
Molecular weight	330 g/l
VOC Content (%)	N/A
Density	8.0 to 8.3 lb/gal
Bulk density	Not applicable

**10. STABILITY AND REACTIVITY****Reactivity**

Not applicable Not applicable

**Chemical stability**

Stable.

**Possibility of Hazardous Reactions**

None under normal use.

**Hazardous polymerization** Hazardous polymerization does not occur.

**Conditions to avoid**

Avoid static discharge. Avoid heat, sparks, and open flame.

**Incompatible materials**

Strong acids. Strong oxidizing agents.

**Hazardous Decomposition Products**

Combustion may produce carbon monoxide, carbon dioxide, and other asphyxiants.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

**Product Information** Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

**Inhalation** Avoid breathing vapors or mists.

**Eye contact** Avoid contact with eyes. Contact with eyes may cause irritation.

**Skin contact** May cause irritation.

**Ingestion** If swallowed, do not induce vomiting. Get medical attention immediately. Not an expected route of exposure.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
Xylene 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Cumene 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	= 39000 mg/m <sup>3</sup> ( Rat ) 4 h > 3577 ppm ( Rat ) 6 h

**Information on toxicological effects**

**Symptoms** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

<b>Skin corrosion/irritation</b>	Can cause skin irritation.
<b>Serious eye damage/eye irritation</b>	Irritating to eyes.
<b>Irritation</b>	Irritating to eyes, respiratory system and skin.
<b>Corrosivity</b>	Not classified.
<b>Sensitization</b>	May cause sensitization of susceptible persons.
<b>Germ cell mutagenicity</b>	This product does not contain any ingredients that cause germ cell mutagenicity.
<b>Carcinogenicity</b>	The table below indicates whether each agency (ACGIH, IARC, NTP, or OSHA) has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	X

**Legend****IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen.

<b>Reproductive toxicity</b>	None known for product as a whole.
<b>Developmental Toxicity</b>	None known for product as a whole.
<b>Teratogenicity</b>	None known.
<b>STOT - single exposure</b>	N/A.
<b>STOT - repeated exposure</b>	N/A.
<b>Aspiration hazard</b>	N/A.

**Numerical measures of toxicity - No information available**

The following values are calculated based on chapter 3.1 of the GHS document For exterior use only. Do not use indoors.

<b>ATEmix (oral)</b>	5,296.00
<b>ATEmix (dermal)</b>	2,383.00
<b>ATEmix (inhalation-dust/mist)</b>	1.57

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

14.75% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Aromatic Naptha (with <0.1% Benzene) 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4 Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
Xylene 1330-20-7	-	13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 780: 96 h Cyprinus carpio mg/L	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48 h water flea mg/L EC50

		LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50	
Cumene 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static 0.6: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

N/A.

**Bioaccumulation**

N/A.

Chemical Name	Partition coefficient
1,2,4 Trimethylbenzene 95-63-6	3.63
Xylene 1330-20-7	3.15
Cumene 98-82-8	3.7

**Other adverse effects**

N/A

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable local, regional, national and international laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** U055 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Cumene 98-82-8	-	-	-	U055

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Cumene 98-82-8	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID no.** UN 1263  
**Proper shipping name** Combustible liquid, n.o.s  
**Hazard Class** 3  
**Packing Group** III  
**Special Provisions** NOT HAZARDOUS FOR TRANSPORTATION UNLESS PACKAGED IN CONTAINERS

WITH A CAPACITY OF 118 GALLONS OR MORE

**TDG** Not regulated.

**MEX** Not regulated.

**ICAO (air)** Not regulated.

**IATA**  
 UN/ID no. UN 1263  
 Proper shipping name PAINT RELATED MATERIAL  
 Hazard Class 3  
 Packing Group III  
 ERG Code 128

**IMDG**  
 UN/ID no. UN 1263  
 Proper shipping name PAINT RELATED MATERIAL  
 Hazard Class 3  
 Packing Group III  
 EmS-No. F-E

**RID** Not regulated.

**ADR** Not applicable in the United States. Not regulated.

**ADN** Not applicable in the United States. Not regulated.

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** All of the components of this product are listed on the US TSCA (Toxic Substances Control Act) Inventory or are exempt.

**DSL/NDSL** All of the components of this product are listed on the DSL.

**Legend:**

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
1,2,4 Trimethylbenzene - 95-63-6	1.0
Xylene - 1330-20-7	1.0
Cumene - 98-82-8	1.0

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Cumene - 98-82-8	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
1,2,4 Trimethylbenzene 95-63-6	X	X	X
Xylene 1330-20-7	X	X	X
Cumene 98-82-8	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties *
<b>HMIS</b>	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection -
<i>Chronic Hazard Star Legend</i>	* = Chronic Health Hazard			

Prepared By  
Issue Date  
Revision Date  
Revision Note  
N/A

Prepared by Top Industrial, Inc.  
05-Sep-2023  
05-Sep-2023

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet